

In-Line mixers

Silverson High Shear mixers are supremely efficient and rapid in operation and are capable of reducing mixing times by up to 90%.

The action of any Silverson In-Line mixer can be modified with the use of rapidly interchangeable workheads. This enables any machine to mix, emulsify, homogenise, solubilise, suspend, disperse and disintegrate solids.


- Aeration free.
- Self pumping.
- No bypassing.
- Interchangeable workheads.
- Hygienic construction.
- Easy maintenance.
- Lower power requirements.
- Eliminates agglomerates and fish eyes.
- Creates stable emulsions and suspensions.
- Reduces particle size.
- Rapidly dissolves solids.
- Accelerates reactions.



How the In-Line works


Stage 1

The high speed rotation of the rotor blades within the precision machined mixing workhead exerts a powerful suction, drawing liquid and solid materials into the rotor/stator assembly.




Stage 2

Centrifugal force then drives materials towards the periphery of the workhead where they are subjected to a milling action in the precision machined clearance between the ends of the rotor blades and the inner wall of the stator.



Stage 3

This is followed by intense hydraulic shear as the materials are forced, at high velocity, out through the perforations in the stator, then through the machine outlet and along the pipework. At the same time, fresh materials are continually drawn into the workhead, maintaining the mixing and pumping cycle.



How to use the In-Line mixer


Recirculation method

This is the most common way of using an In-Line mixer, providing a higher degree of homogenisation and particle size reduction. Here product is drawn from the bottom of the vessel, processed through the high shear rotor/stator workhead and passed back into the top of the vessel.

In small vessels this will ensure adequate in-tank movement, but in larger vessels an auxiliary in-tank mixer or agitator will be required.

Additional fluid ingredients can be fed into the workhead and uniformly mixed before entering the vessel.

Where quality assurance (QA) demands a set number of passes through the rotor/stator workhead, product can be passed back and forth between two separate vessels.



Single pass method

There are basically three types of operations for which single pass processing can be used.

Continuous blending


Ingredients are metered into the mixer or a manifold just prior to the rotor/stator workhead. This ensures that products that react together are mixed immediately on contact. This method is ideal for continuous liquid/liquid blending and for products where aeration must be avoided, e.g., detergents.

Series processing

In cases where a higher degree of homogenisation or comminution is required than can be obtained by a single pass through the In-Line mixer, it is possible to achieve the required results by using two or more machines in series.

Premix method

The ingredients are coarsely premixed in a holding vessel with a Silverson Batch mixer, Ultramix or a simple agitator. A single pass through the In-Line mixer will then ensure an agglomerate-free, homogeneous product. All the product must pass through the In-Line mixer's rotor/stator workhead as bypassing is impossible.



Technical specifications

Materials of construction

Product contact parts in 316L stainless steel. Special materials on request.

Motors

TEFV (Totally Enclosed Fan Ventilated) and ATEX approved flameproof motors are standard. Inverter rated, stainless steel and other motors are optional extras.

Operating pressures

Designed for operation on pressures of up to 150 psi (10 bar). Higher pressure units are available on request.

Inlet and outlet connections

All standard sanitary screw or flange fittings are available on request (e.g., ISS, DIN, RJT, SMS, Tri-clamp, etc.). Tangential self-draining outlet; can be rotated for vertical self-venting configuration.

Sealing

Ultra hygienic EHEDG Approved single and double mechanical shaft seals, easily converted from one to the other, according to application.

Interchangeable workheads

Single stage rotor/stator configurations as standard. For those applications which require greater shear, interchangeable multistage configurations can be used.



General purpose disintegrating head



General purpose disintegrating head, multistage inner and outer



Slotted disintegrating head



Slotted disintegrating head, multistage inner and outer



Square hole high shear screen™



Combined configuration: inner general purpose with outer slotted disintegrating head



Emulsor screen



Combined configuration: inner slotted with outer square hole high shear screen™

General duty In-Line mixers

Silverson offers a range of In-Line mixers suitable for hazardous and aggressive chemical service. These units are of robust and simple construction, which ensures that maintenance is easy and downtime minimal.

With some of the highest rotor tip speeds and shear rates in the industry, production times can be cut by up to 90%, reducing mechanical wear and maintenance requirements, while offering better particle size reduction, emulsification, rapid solubilisation and dispersion.

Optional features

- Jacketed units for temperature sensitive products.
- Non-standard materials of construction such as hastelloy, titanium and hardened steels for processing highly abrasive or corrosive products.
- High capacity units with self-pumping capacities from 220 litres up to 300,000 litres per hour.

Typical Applications

Bitumens, Edible oil refining, Drilling muds, Adhesives, Luboils, Pigment dispersions, Titanium dioxide, etc.

